



Wuxi Shenbing Bearing Company Limited



7003 ACD/P4A Bearing 2D drawings and 3D CAD models

17 mm x 35 mm x 10 mm SKF 7003 ACD/P4A
angular contact ball bearings

Bearing No. 7003 ACD/P4A

| | |
|---|-------------|
| Size | 35x17x10 mm |
| Bore Diameter | 35 mm |
| Outer Diameter | 17 mm |
| Width | 10 mm |
| d | 17 mm |
| D | 35 mm |
| B | 10 mm |
| d ₁ | 22.6 mm |
| d ₂ | 22.6 mm |
| D ₁ | 29.3 mm |
| r _{1,2} - min. | 0.3 mm |
| r _{3,4} - min. | 0.2 mm |
| a | 11.2 mm |
| d _a - min. | 19 mm |
| d _b - min. | 19 mm |
| D _a - max. | 33 mm |
| D _b - max. | 33.6 mm |
| r _a - max. | 0.3 mm |
| r _b - max. | 0.2 mm |
| d _n | 23.7 mm |
| Basic dynamic load rating - C | 6.5 kN |
| Basic static load rating - C ₀ | 3.1 kN |
| Fatigue load limit - P _u | 0.132 kN |
| Limiting speed for grease | 45000 r/min |



Wuxi Shenbing Bearing Company Limited

| | |
|------------------------------------|----------------------|
| Lubrication | |
| Limiting speed for oil lubrication | 70000 mm/min |
| Ball - D_w | 5.556 mm |
| Ball - z | 12 |
| G_{ref} | 0.54 cm ³ |
| Calculation factor - e | 0.68 |
| Calculation factor - Y_2 | 0.87 |
| Calculation factor - Y_0 | 0.38 |
| Calculation factor - X_2 | 0.41 |
| Calculation factor - Y_1 | 0.92 |
| Calculation factor - Y_2 | 1.41 |
| Calculation factor - Y_0 | 0.76 |
| Calculation factor - X_2 | 0.67 |
| Preload class A - G_A | 40 N |
| Preload class B - G_B | 80 N |
| Preload class C - G_C | 160 N |
| Preload class D - G_D | 320 N |
| Calculation factor - f | 1.04 |
| Calculation factor - f_1 | 0.99 |
| Calculation factor - f_{2A} | 1 |
| Calculation factor - f_{2B} | 1.02 |
| Calculation factor - f_{2C} | 1.05 |
| Calculation factor - f_{2D} | 1.08 |
| Calculation factor - f_{HC} | 1 |
| Preload class A | 48 N/micron |
| Preload class B | 62 N/micron |
| Preload class C | 81 N/micron |
| Preload class D | 107 N/micron |
| | |



Wuxi Shenbing Bearing Company Limited

| | |
|------------------------|--|
| Category | Precision Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.042 |
| EAN | 7316570721355 |
| Product Group | B04270 |
| Enclosure | Open |
| Precision Class | ABEC 7 ISO P4 |
| Material - Ball | Steel |
| Number of Bearings | 1 (Single) |
| Contact Angle | 25 Degree |
| Preload | None |
| Raceway Style | 1 Rib Outer Ring |
| Cage Material | Phenolic |
| Rolling Element | Ball Bearing |
| Flush Ground | No |
| Inch - Metric | Metric |
| Other Features | Single Row Angular Contact High Precision |
| Long Description | 17MM Bore; 35MM Outside Diameter; 10MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball Material; 1 (Single) Bearings; 25 Degree Contact Angle; Phenolic Cage Material; 1 Rib Outer Ring Rac |
| Category | Precision Ball Bearings |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact Ball |
| Manufacturer URL | http://www.skf.com |



Wuxi Shenbing Bearing Company Limited

| | |
|-------------------------------|--------------------------------------|
| Manufacturer Item Number | 7003 ACD/P4A |
| Weight / LBS | 0.093 |
| Width | 0.394 Inch 10 Millimeter |
| Bore | 0.669 Inch 17 Millimeter |
| Outside Diameter | 1.378 Inch 35 Millimeter |
| bore diameter: | 17 mm |
| radial static load capacity: | 3.1 kN |
| outside diameter: | 35 mm |
| maximum rpm (grease): | 45000 rpm |
| overall width: | 10 mm |
| maximum rpm (oil): | 70000 rpm |
| contact angle: | 25 ° |
| bearing material: | Steel |
| duplex type: | Duplex Universal |
| cage material: | Cotton Fabric Reinforced Phenolic |
| closure type: | Open |
| fillet radius: | 0.3 mm |
| precision rating: | P4 |
| series: | 70 |
| operating temperature range: | 300 ° F |
| manufacturer product page: | Click here |
| radial dynamic load capacity: | 6.5 kN |
| manufacturer upc number: | 7316570721355 |
| d ₁ | 22.6 mm |
| d ₂ | 22.6 mm |
| D ₁ | 29.3 mm |
| r _{1,2} min. | 0.3 mm |
| r _{3,4} min. | 0.2 mm |
| d _a min. | 19 mm |
| d _b min. | 19 mm |
| | |



Wuxi Shenbing Bearing Company Limited

| | |
|--|----------------------|
| D_a max. | 33 mm |
| D_b max. | 33.6 mm |
| r_a max. | 0.3 mm |
| r_b max. | 0.2 mm |
| d_n | 23.7 mm |
| Basic dynamic load rating C | 6.5 kN |
| Basic static load rating C_0 | 3.1 kN |
| Fatigue load limit P_u | 0.132 kN |
| Attainable speed for grease lubrication | 45000 r/min |
| Attainable speed for oil-air lubrication | 70000 r/min |
| Ball diameter D_w | 5.556 mm |
| Number of balls z | 12 |
| Reference grease quantity G_{ref} | 0.54 cm ³ |
| Preload class A G_A | 40 N |
| Static axial stiffness, preload class A | 48 N/μm |
| Preload class B G_B | 80 N |
| Static axial stiffness, preload class B | 62 N/μm |
| Preload class C G_C | 160 N |
| Static axial stiffness, preload class C | 81 N/μm |
| Preload class D G_D | 320 N |
| Static axial stiffness, preload class D | 107 N/μm |
| Calculation factor f | 1.04 |
| Calculation factor f_1 | 0.99 |
| Calculation factor f_{2A} | 1 |
| Calculation factor f_{2B} | 1.02 |
| Calculation factor f_{2C} | 1.05 |
| Calculation factor f_{2D} | 1.08 |
| | |



Wuxi Shenbing Bearing Company Limited

| | |
|---|----------|
| Calculation factor f_{HC} | 1 |
| Calculation factor e | 0.68 |
| Calculation factor (single, tandem) Y_2 | 0.87 |
| Calculation factor (single, tandem) Y_0 | 0.38 |
| Calculation factor (single, tandem) X_2 | 0.41 |
| Calculation factor (back-to-back, face-to-face) Y_1 | 0.92 |
| Calculation factor (back-to-back, face-to-face) Y_2 | 1.41 |
| Calculation factor (back-to-back, face-to-face) Y_0 | 0.76 |
| Calculation factor (back-to-back, face-to-face) X_2 | 0.67 |
| Mass bearing | 0.038 kg |